

Escape

Produktbeskrivelse



ege

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
Konstruktion		
Struktur	ISO 2424	Tuftet loop pile strukturvævet
Gauge	ISO 2424	1/12
Luvmateriale	DIR 96/73, 96/74	100% regenerated Econyl PA6
Farvemethode	-	Millitron farvet
Bagside	eTL	HL - High foam
Dimensioner	ISO 3018	Approx. 400 cm
Totalhøjde	eTL	Ca. 9,5 mm.
Slidlag	eTL	Ca. 3,5 mm.
Noppeantal	ISO 1763	Ca. 198.000 pr.m2
Totalvægt	ISO 8543	Ca. 2.800 g/m2
Luvindsatsvægt	eTL	950 g/m2
	.	28.03 oz./yd2

Egnethedsprøvnings

Brugsområder	eTL	23 - Bolig - Kraftig brug
Garanti	eTL	Garanti mod gennemslid 10 år
Trappeegnet	eTL	Ja
Antistatiske egenskaber	eTL	Permanent antistatisk
Gulvarmeegnet	eTL	Ca. 0,16 m2K/W
Lysrefleksion	eTL	Testrapport

Sikkerhed & Miljø

CE Mærkning	EN 14041	Certificeret
	Ydeevnedeklaration	DOP E
	Ce Year	15
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Skridsikkerhed EN 13893	Class DS

Vejledninger

Montering, inkl. limguide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Producent

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC



THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

ege

THE URGE TO EXPLORE SPACE