

Una Grano Ecotrust

Produktbeskrivelse



ege

THE URGE TO EXPLORE SPACE

| Produktbeskrivelse | Metoder | Produktdata |
|----------------------------|------------------|-----------------------------|
| Konstruktion | | |
| Struktur | ISO 2424 | Tuftet loop pile |
| Gauge | ISO 2424 | 5/64 |
| Luvmateriale | DIR 96/73, 96/74 | 100% polyamid |
| Farvemethode | - | Forfarvet garn |
| Bagside | eTL | Ecotrust 350, 100% recycled |
| Dimensioner | ISO 3018 | 48x48/96x96/24x96cm/Figura |
| Dimensionstabilitet fliser | EN 986 | <0,2% |
| Totalhøjde | ISO 1765 | Ca. 7,0 mm. |
| | . | 0.28" |
| Slidlag | ISO 1766 | Ca. 3,0 mm. |
| Noppeantal | ISO 1763 | Ca. 167.000 pr.m2 |
| Totalvægt | ISO 8543 | Ca. 2.800 g/m2 |
| | . | 82.6 oz./yd2 |
| Luvindsatsvægt | eTL | 570 g/m2 |
| | . | 16.82 oz./yd2 |
| Luvdensitet | ISO 8543. | Ca. 0,125 g/cm3 |

Egnethedsprøvnninger

| | | |
|-------------------------------|--------------|-----------------------------|
| Brugsområder | EN 1307 | 33 - Erhverv - Kraftig brug |
| Garanti | eTL | Contract certifikat |
| Brugsområder | Gulvbranchen | Klasse 33 |
| Rullehjulseget | EN 985 | Ja, konstant brug |
| Trappeget | EN 1963 | Ja |
| Antistatiske egenskaber | eTL | Permanent antistatisk |
| Personopladning | ISO 6356 | Antistatisk |
| Trinlydsdæmpning | eTL | 25 dB |
| Akustisk absorption | eTL | 0,25 aW |
| Gulvarmeegnet | eTL | Ca. 0,12 m2K/W |
| Lysrefleksion | eTL | Testrapport |
| Lysægthed | ISO 105-B02 | >5 |
| | AATCC 16 | 5.0 |
| Gnideægthed våd | ISO 105-X12 | >3 |
| Gnideægthed tør | ISO 105-X12 | >3-4 |
| Vandægthed mønstrede/melerede | ISO 105-E01 | >4 |

Sikkerhed & Miljø

| | | |
|---------------------|---------------------------|-------------------|
| Brandklassifikation | VKF/AEAI | Godkendt |
| | ASTM E-648 | Class 1 |
| | ASTM E662 Smoke Density | <450 |
| | ASTM D2859 Surface Flamm. | Pass |
| | EN 13501-1 Euroclass | Bfl-s1 |
| CE Mærkning | EN 14041 | Certificeret |
| | CPR | 1021-CPR-010-1/16 |
| | Ydeevnedeklaration | DOP 5B-PA-ECT350 |
| | Notified body no. | 1021 |

| Produktbeskrivelse | Metoder | Produktdata |
|--------------------|--------------------------------|----------------------------|
| Indeklima | Ce Year | 17 |
| | Content of PCP EN 12673 | DL |
| | Formaldehyde emission | NA |
| | Skridsikkerhed EN 13893 | Class DS |
| | Green Label Plus | Godkendt |
| | Emissions dans l'air intérieur | A+/A+ |
| | Indoor Air Comfort Gold | Group 3 |
| Miljø | ABG | ABG-28-01-03-03-2018 |
| | BRE | ENP 434 |
| | Byggvarudeklaration | eBVD |
| | BREEAM-NOR | Med ECTA bagside |
| | Cradle To Cradle Certified | Ecotrust, Bronze certified |
| | Recycled Content, ISO 14021 | Ca. 16,4 % |
| | Recycled Content for LEED | Ca. 16,4 % |

Vejledninger

| | | | |
|---------------------------|-------------------------|--------------|----------|
| Montering, inkl. limguide | DK | Dansk | |
| | N | Norsk | |
| | S | Svensk | |
| | GB | English | |
| | D | Deutsch | |
| | F | Francais | |
| | Lægningsretning | Quarter turn | |
| Montering fliser | Rengøring, pletfjerning | DK | Dansk |
| | | N | Norsk |
| | | S | Svensk |
| | | GB | English |
| | | D | Deutsch |
| | | F | Francais |

Producent

| | | |
|----------------------|-----------|-------------------------------|
| Fabrikscertificering | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | DS/OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |



THE URGE TO EXPLORE SPACE