

Una Tinta Ecotrust

Produktbeskrivelse



ege

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
Konstruktion		
Struktur	ISO 2424	Tuftet loop pile strukturvævet
Gauge	ISO 2424	1/12
Luvmateriale	DIR 96/73, 96/74	100% polyamid
Farvemethode	-	Forfarvet garn
Bagside	eTL	Ecotrust 350, 100% recycled
Dimensioner	ISO 3018	48x48/96x96/24x96cm/Figura
Totalhøjde	ISO 1765	Ca. 9,5 mm.
	.	0.37"
Slidlag	ISO 1766	Ca. 6,0 mm.
Noppeantal	ISO 1763	Ca. 249.100 pr.m2
Totalvægt	ISO 8543	Ca. 3.150 g/m2
	.	92.93 oz./yd2
Luvindsatsvægt	eTL	950 g/m2
	.	28.03 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,145 g/cm3

Egnethedsprøvnninger

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
Garanti	eTL	Contract certifikat
Rullehjulseget	EN 985	Ja, konstant brug
Trappeget	EN 1963	Ja
Antistatiske egenskaber	eTL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	eTL	28 dB
Akustisk absorption	eTL	0,25 aW
Gulvarmeegnet	eTL	Ca. 0,16 m2K/W
Lysægthed	ISO 105-B02	>5
Gnideægthed våd	ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed mønstrede/melerede	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Øvrige brugstests	ASTM D5252 Hexapod	3.0/4.0
	AATCC 134 Electrostatic propensity	1.4 kV

Sikkerhed & Miljø

Brandklassifikation	VKF/AEAI	Godkendt
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	ASISO 9239.1-2003	8,40 KW/m2
CE Mærkning	EN 14041	Certificeret

Produktbeskrivelse	Metoder	Produktdata
Indeklima	CPR	1021-CPR-009-1/16
	Ydeevnedeklaration	DOP 5B-PA-ECT350
	Notified body no.	1021
	Ce Year	16
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Skridsikkerhed EN 13893	Class DS
	Green Label Plus	Godkendt
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 3
Miljø	ABG	ABG-28-01-03-03-2018
	BRE	ENP 434
	BREEAM-NOR	Med ECTA bagside
	Environmental Product Decl.	EPD-EGE-20160220-CBC1-EN
	Cradle To Cradle Certified	Ecotrust, Bronze certified
	Recycled Content, ISO 14021	Ca. 14,5 %
	Recycled Content for LEED	Ca. 14,5 %

Vejledninger

Montering, inkl. limguide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Montering fliser	Lægningsretning	Quarter turn/ monolithic
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Producent

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE